



Protime T&A Solutions

IT31

IT Series terminals are ideal for improving business efficiency and monitoring employee productivity. The IT31 builds upon the key features of the IT11 by offering customisation and compatibility with a wider range of credential options.



IT31 Time & Attendance Terminal

IT Series Workforce Management Terminals are ideal for improving business efficiency and monitoring employee productivity. IT31 builds upon the key features of the IT11 by offering customisation and compatibility with a wider range of credential options.

Easy

The IT31 is easy to use, with Clock in/out functions, Multi-Cost clocking functions, Absence clocking functions and many other possibilities.

Plug and play deployment means the IT31 is also easy to install. Allowing you to install more terminals in a shorter amount of time, increasing your installation capacity.

Optional WiFi modules make it even easier to install the terminals within environments without physical ethernet connections.

Robust

The IT31's durable casing and membrane keypad means the terminal is designed to last in harsh working environments.

In addition, its internal battery backup module means that the terminal is fully functional in the event of a power outage, ensuring users can always capture reliable data.

The IT31 also has an optional environmental enclosure which ensures the clock is operational in temperatures as low as -18°C.

End User Benefits:

Clock hardware tailored to your needs, for example, offering a range of reader technologies as required, i.e. biometric readers for an additional layer of security.

Multi-lingual Interface possibilities.

Possibility to connect USB Barcode Scanners

Display

Graphical 2.7inch display

High resolution matrix display

Personalised welcome screen i.e. display time or prompts



Keypad

Durable membrane keyboard with numeric keypad, navigation and function keys

Key operation beep provides live confirmation

Power

12Vdc jack

IEEE802.3af POE

Back-up internal lithium-polymer battery option which lasts for up to 3 hours.

Operating temperature

-10 to +50°C (14 to 122°F)

Optional Environment enclosure: -18°C or 0°F

Humidity 5-90% non-condensing

RTC

Battery backed real time clock

Use internal clock

System supports NTP for setting and maintaining time

Case

Size 198 x 220 x 105 mm (w x h x d)
7.8 x 8.6 x 4.1 inches (w x h x d)

Pre-formed cable entries

I/O

Multi Protocol Reader
Possibilities (Mifare, Legic, Hid, etc)

Programmable Relay Output

External Barcode Scanner, Biometric

Connectivity

Ethernet HTTPS connectivity

Wi-Fi option through USB

More info?

Contact Prottime at

Prottime
Kontichsesteenweg 54
2630 Aartselaar

+32 (0)3 870.60.50

make
time
valuable