



Protime T&A Solutions

IT51

IT Series terminals are ideal for improving business efficiency and monitoring employee productivity. The IT51 provides many benefits including by offering customisation and compatibility with a wider range of credential options.



IT51 Time & Attendance Terminal

IT Series Workforce Management Terminals are ideal for improving business efficiency and monitoring employee productivity. The IT51 provides many benefits including by offering customisation and compatibility with a wider range of credential options.

Easy

The IT51's compatibility with a wide range of credentials ensures that it easily integrates with any organisation.

The IT51 is an ideal choice for multi-lingual workforces, as the interface can change to the individual's preferred language when they present their credential.

Plug and play deployment means the IT51 is also easy to install. Allowing you to install more terminals in a shorter amount of time, increasing your installation capacity.

Optional WiFi modules make it even easier to install the terminals within environments without physical ethernet connections.

Robust

The IT51's durable casing ensures it endures in all working environments. In addition, the optional environmental enclosure ensures the clock is operational in temperatures as low as -18°C.

In addition, its internal optional battery backup module means that the terminal is fully functional in the event of a power outage, ensuring users can always capture reliable data.

End User Benefits:

Clock hardware tailored to your needs, for example, offering a range of reader technologies as required, i.e. biometric readers for an additional layer of security.

Multi-lingual Interface possibilities.

Possibility to connect USB Barcode Scanners

Display

Ten-inch touch screen LCD TFT colour display

High resolution with LED backlight

Personalised welcome screen i.e. display time or prompts



Keypad

Durable membrane keyboard with numeric keypad, navigation and function keys

Key operation beep provides live confirmation

Power

12Vdc jack

IEEE802.3af POE

Back-up internal lithium-polymer battery option which lasts for up to 3 hours.

Active IR presence detection for energy saving when the clock is not being used

Operating temperature

-10 to +50°C (14 to 122°F)

Optional Environment enclosure: -18°C or 0°F

Humidity 5-90% non-condensing

Optional screen protector

RTC

Battery backed real time clock

Use internal clock

System supports NTP for setting and maintaining time

Case

Size 256 x 241 x 105 mm (w x h x d)

10.1 x 9.5 x 4.1 inches (w x h x d)

Pre-formed cable entries

I/O

Multi Protocol Reader Possibilities (Mifare, Legic, Hid, etc)

Programmable Relay Output

External Barcode Scanner, Biometric

Connectivity

Ethernet HTTPS connectivity

Wi-Fi option through USB

More info?

Contact Prottime at

Prottime
Kontichsesteenweg 54
2630 Aartselaar

+32 (0)3 870.60.50

make
time
valuable